
AKZM 8480 WH

12NC: 852584801110

GTIN (EAN) code: 8003437832994







Product group Oven Commercial code AKZM 8480 WH Main colour of product White Construction type Built-in Type of control Mechanical and electronic Type of control settings - Are any hobs controls integrated? Ne Which kind of hobs can be controlled? - Automatic programmes Yes Current (A) 16 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 90 Plug type Ne Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 595 Width of the product 595 Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 39.5 Usable volume (of cavity) 73 Integrated Cleaning system Pyrolytic Grids of the cavity 1 Trays 2	MAIN FEATURES	
Main colour of productWhiteConstruction typeBuilt-inType of controlMechanical and electronicType of control settings-Are any hobs controls integrated?NeWhich kind of hobs can be controlled?-Automatic programmesYesCurrent (A)16Voltage (V)220-240Frequency (Hz)50/60Length of Electrical Supply Cord (cm)90Plug typeNeDepth with open door 90 degree (mm)-Height of the product595Width of the product595Width of the product564Minimum niche height0Niche depth0Net weight (kg)39.5Usable volume (of cavity)73Integrated Cleaning systemPyrolyticGrids of the cavity1	Product group	0ven
Type of control Type of control Type of control settings Are any hobs controls integrated? Which kind of hobs can be controlled? Automatic programmes Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Depth with open door 90 degree (mm) Height of the product Sp5 Width of the product Minimum niche height Minimum niche width Net weight (kg) Usable volume (of cavity) Type of control Mechanical and electronic Frequency Plug Yes 220-240 Frequency (Hz) 50/60 220-240 Frequency (Hz) 50/60 Plug type Ne Popth with open door 90 degree (mm) - Height of the product 595 Width of the product 595 Usable volume (of cavity) Ta Integrated Cleaning system Pyrolytic Grids of the cavity 1	Commercial code	AKZM 8480 WH
Type of control Type of control settings Are any hobs controls integrated? Which kind of hobs can be controlled? Automatic programmes Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Depth with open door 90 degree (mm) Height of the product Depth of the product Mechanical and electronic Yes Current (A) 16 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) Plug type Ne Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 595 Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth Ne Neweight (kg) 39.5 Usable volume (of cavity) Ta Integrated Cleaning system Pyrolytic Grids of the cavity	Main colour of product	White
Type of control Type of control settings Are any hobs controls integrated? Which kind of hobs can be controlled? Automatic programmes Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Ne Depth with open door 90 degree (mm) Height of the product Sp5 Width of the product Minimum niche height O Net weight (kg) Usable volume (of cavity) Integrated Cleaning system Per Whe Ne Per Me Relectronic 1- Ne Relectronic 1- Ne 16 No Ne 220-240 Frequency (Hz) 50/60 220-240 Frequency (Hz) 50/60 10 10 10 10 10 10 10 10 10	Construction type	Built-in
Are any hobs controls integrated? Which kind of hobs can be controlled? Automatic programmes Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Depth with open door 90 degree (mm) Height of the product Depth of the product S95 Width of the product Minimum niche height O Net weight (kg) Net weight (kg) Japan 1 Japan 2 Japan 2 Japan 2 Japan 3 Japan 4 Japan 4	Type of control	
Which kind of hobs can be controlled? Automatic programmes Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Ne Depth with open door 90 degree (mm) Height of the product S95 Width of the product 595 Width of the product 595 Depth of the product Minimum niche height O Niche depth Ne Net weight (kg) 39.5 Usable volume (of cavity) Integrated Cleaning system Pyrolytic Grids of the cavity 1	Type of control settings	-
Automatic programmes Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Ne Depth with open door 90 degree (mm) Height of the product S95 Width of the product 595 Width of the product 595 Depth of the product 564 Minimum niche height 0 Niche depth Ne Net weight (kg) 39.5 Usable volume (of cavity) Integrated Cleaning system Pyrolytic Grids of the cavity 1	Are any hobs controls integrated?	Ne
Current (A) 16 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 90 Plug type Ne Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 595 Depth of the product 595 Depth of the product 564 Minimum niche height 0 Miche depth 0 Net weight (kg) 39.5 Usable volume (of cavity) 73 Integrated Cleaning system Pyrolytic Grids of the cavity 1	Which kind of hobs can be controlled?	-
Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 90 Plug type Ne Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 595 Depth of the product 595 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 39.5 Usable volume (of cavity) 73 Integrated Cleaning system Pyrolytic Grids of the cavity 1	Automatic programmes	Yes
Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 90 Plug type Ne Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 595 Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 39.5 Usable volume (of cavity) 73 Integrated Cleaning system Pyrolytic Grids of the cavity 1	Current (A)	16
Length of Electrical Supply Cord (cm) Plug type Depth with open door 90 degree (mm) Height of the product S95 Width of the product Depth of the product Minimum niche height Niche depth Net weight (kg) Usable volume (of cavity) Integrated Cleaning system Pyrolytic Grids of the cavity Pues Pound (cm) Pou	Voltage (V)	220-240
Plug type Ne Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 595 Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 39.5 Usable volume (of cavity) 73 Integrated Cleaning system Pyrolytic Grids of the cavity 1	Frequency (Hz)	50/60
Depth with open door 90 degree (mm) Height of the product S95 Width of the product Depth of the product S95 Depth of the product Minimum niche height Minimum niche width Niche depth Net weight (kg) Usable volume (of cavity) Integrated Cleaning system Pyrolytic Grids of the cavity	Length of Electrical Supply Cord (cm)	90
Height of the product 595 Width of the product 595 Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 39.5 Usable volume (of cavity) 73 Integrated Cleaning system Pyrolytic Grids of the cavity 1	Plug type	Ne
Width of the product 595 Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 39.5 Usable volume (of cavity) 73 Integrated Cleaning system Pyrolytic Grids of the cavity 1	Depth with open door 90 degree (mm)	-
Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 39.5 Usable volume (of cavity) 73 Integrated Cleaning system Pyrolytic Grids of the cavity 1	Height of the product	595
Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 39.5 Usable volume (of cavity) 73 Integrated Cleaning system Pyrolytic Grids of the cavity 1	Width of the product	595
Minimum niche width 0 Niche depth 0 Net weight (kg) 39.5 Usable volume (of cavity) 73 Integrated Cleaning system Pyrolytic Grids of the cavity 1	Depth of the product	564
Niche depth 0 Net weight (kg) 39.5 Usable volume (of cavity) 73 Integrated Cleaning system Pyrolytic Grids of the cavity 1	Minimum niche height	0
Net weight (kg) 39.5 Usable volume (of cavity) 73 Integrated Cleaning system Pyrolytic Grids of the cavity 1	Minimum niche width	0
Usable volume (of cavity) 73 Integrated Cleaning system Pyrolytic Grids of the cavity 1	Niche depth	0
Integrated Cleaning system Pyrolytic Grids of the cavity 1	Net weight (kg)	39.5
Grids of the cavity 1	Usable volume (of cavity)	73
3	Integrated Cleaning system	Pyrolytic
Trays 2	Grids of the cavity	1
	Trays	2

TECHNICAL FEATURES	
Timer	-
Time control	Electronic
Time-setting options	Start and Stop
Safety device	-
Interior light	Yes
Number of interior lights of the cavity	1
Position of interior lights of the cavity	Rear
Oven guides of the cavity	Telescopic
Probe of the cavity	Ne

ENERGY LABEL	
Energy input	Electric
Type of energy of the cavity	Electrică
Energy efficiency class - NEW (2010/30/EU)	A+
Energy consumption per cycle conventional - NEW (2010/30/EU)	0.91
Energy consumption per cycle forced air convection - NEW (2010/30/EU)	0.7